

PROXIMITY SENSOR

■ Cylindrical DC 2-wire type (Power: 24VDC)



Appearance		Appearance Classification				Sensing distance (mm)	Response frequency (Hz)	Model
		Standard type		Long type				
		Shield	Non-shield	Shield	Non-shield			
M08	Normal type					1.5	800	PRT08-1.5DO PRT08-1.5DC
						2		PRT08-2DO PRT08-2DC
	Connector type					1.5		PRWT08-1.5DO PRWT08-1.5DC
						2		PRWT08-2DO PRWT08-2DC
M12	Normal type					2	800	PRT12-2DO PRT12-2DC
						4		PRT12-4DO PRT12-4DC
	Connector type					2	800	PRCMT12-2DO PRCMT12-2DC
						4		PRCMT12-4DO PRCMT12-4DC
	Cable outgoing connector type					2	800	PRWT12-2DO PRWT12-2DC
						4		PRWT12-4DO PRWT12-4DC
Spatter resistance type					2	800	PRAT12-2DO PRAT12-2DC	
M18	Normal type					5	350	PRT18-5DO PRT18-5DC
						8		PRT18-8DO PRT18-8DC
	Connector type					5	350	PRCMT18-5DO PRCMT18-5DC
						8		PRCMT18-8DO PRCMT18-8DC
	Cable outgoing connector type					5	350	PRWT18-5DO PRWT18-5DC
						8		PRWT18-8DO PRWT18-8DC
Spatter resistance type					5	350	PRAT18-5DO PRAT18-5DC	
M30	Normal type					10	250	PRT30-10DO PRT30-10DC
						15		PRT30-15DO PRT30-15DC
	Connector type					10	250	PRCMT30-10DO PRCMT30-10DC
						15		PRCMT30-15DO PRCMT30-15DC
	Cable outgoing connector type					10	250	PRWT30-10DO PRWT30-10DC
						15		PRWT30-15DO PRWT30-15DC
Spatter resistance type					10	250	PRAT30-10DO PRAT30-10DC	

▶ IEC Connector type in IEC standard is currently being developed. Please add "-I" to the end of model for an order.